

# Christie CDXL and CXL Data Sheet

CDXL and CXL power, lumens, air extraction and warranty info

CP2000-S/X					
Lamp	Nom. Lamp Power (Watts)	Nominal Lumens Actual <sup>‡</sup>	CFM Requirement	Warranty (hours)	Estimated Average Expected Life (hours)
CXL-20^	2000	6000	450	100% to 2400	3500
CDXL-20	2000	8500	450	100% to 2400	3500
CXL-30	3000	10250	450	100% to 1500	2500
CDXL-30	3000	13000	450	100% to 1500	2500
CXL-45	4500	14750	600	100% to 1200	1500
CXL-60	6000	16750	600	100% to 600	900
CDXL-45	4500	19500	600	100% to 1000	1200
CDXL-60	6000	22000	600	100% to 600	900

CP2000-SB/XB					
Lamp	Nom. Lamp Power (Watts)	Nominal Lumens Actual <sup>‡</sup>	CFM Requirement	Warranty (hours)	Estimated Average Expected Life (hours)
CXL-20^	2000	8000	450	100% to 2400	3500
CDXL-20	2000	11750	450	100% to 2400	3500
CXL-30	3000	15000	450	100% to 1500	2500
CDXL-30	3000	18500	450	100% to 1500	2500
CXL-45	4500	20000	600	100% to 1200	1500
CXL-60	6000	24000	600	100% to 600	900
CDXL-45	4500	26500	600	100% to 1000	1200
CDXL-60	6000	30000	600	100% to 600	900

# Christie CDXL and CXL Data Sheet

CDXL and CXL power, lumens, air extraction and warranty info

## CP2000-M

Lamp	Nom. Lamp Power (Watts)	Nominal Lumens Actual†	CFM Requirement	Warranty (hours)	Estimated Average Expected Life (hours)
CDXL-18SD	1800	11000	450†	100% to 1750	2100*
CDXL-20SD	2000	13000	450†	100% to 1000	1500**

## CP2000-ZX

Lamp	Nom. Lamp Power (Watts)	Nominal Lumens Actual†	CFM Requirement	Warranty (hours)	Estimated Average Expected Life (hours)
CXL-20^	2000	6000	450	100% to 2400	3500
CDXL-20	2000	8700	450	100% to 2400	3500
CDXL-30	3000	15000	450	100% to 1500	2500
CDXL-30SD	3000	18500	450	100% to 1000	1500***

† Exhaust extraction is optional. Extraction with the optional extraction duct requires 450CFM

‡ Color corrected / center lumens

^ Requires the purchase of an adapter

\* 2100 hours when operated in a CP2000-M model number ending in -02 or greater

\*\* 1500 hours when operated in a CP2000-M model number ending in -02 or greater. Not recommended for use in CP2000-M model number ending in -01

\*\*\* 1500 hours when operated in a CP2000-ZX

### Corporate offices

Christie Digital Systems USA, Inc  
USA – Cypress  
ph: 714 236 8610  
Christie Digital Systems Canada, Inc.  
Canada – Kitchener  
ph: 519 744 8005

### Worldwide offices

United Kingdom ph: +44 118 977 8000	Eastern Europe and Russian Federation ph: +36 (0) 1 47 48 100	India ph: (080) 41468941 - 48	China (Beijing) ph: +86 10 6561 0240
Germany ph: +49 2161 664540	Dubai (United Arab Emirates) ph: +971 (0) 4 299 7575	Singapore ph: +65 6877 8737	Japan (Tokyo) ph: +81 3 3599 7481
France ph: +33 (0) 1 41 21 44 04		China (Shanghai) ph: +86 21 6278 7708	Korea (Seoul) ph: +82 2 702 1601

### Independent sales consultant offices

Spain  
ph: +34 91 633 9990  
Italy  
ph: +39 (0) 2 9902 1161  
South Africa  
ph: +27 (0) 317 671 347



For the most current specification information, please visit [christiedigital.com](http://christiedigital.com)



Copyright 2009 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Performance specifications are typical unless otherwise noted. Performance specifications are based on information available at the time of printing. Every effort has been made to ensure accuracy, however in some cases changes or product delays could occur which may not be reflected in this brochure. Christie Digital Systems USA, Inc. reserves the right to make changes without notice or obligation. Printed on recycled paper. Lamp data sheet August 09.

**CHRISTIE®**